BRT

Quality & Innovative Fire & Rescue Equipment

Positive Pressure Ventilation

GROUPE LEADER®

Tomorrow's technology today

Features:

- Powerful "Turbine" action
- High-speed smoke clearance
  Smoke spread containment
- Improved visibility
- Reduced temperature and toxicity
- Reduced risk of flashover
- Shorter operation time
- Low bulk - Robust construction
- Easy maintenance
  Standard reliable engine
  Life time guarantee on ignition
- Conforms to CE standards
- Guarantee : 2 years

MT 236 shown

Protective Cover

Discharge and Extraction Duct

FEATURES OF MT 200 SERIES

Model	Engine	Autonomy At full speed	Dimensions L x H x W (cm)	Weight (kg)
MT 224	3,5 CV Briggs/4-stroke	1 ½ hour	55 x 56,5 x 41	28,7
MT 236	6 CV Briggs / 4-stroke	1 ½ hour	56 x 53 x 48	37,5
MT 260	9 CV Briggs / 4-stroke	2 ½ hour	73 x 71,5 x 57	59,5
MT 296	18 CV Briggs / 4-stroke	1 ¼ hour	73 x 71,5 x 57	68,5

Other models available including conventional, electric and intrinsically safe.
Full catalogue available on request.

For further information contact:
BRT Fire and Rescue
Ph: (07) 3287 5504
Fax: (07) 3287 5505
PO Box 55 Ormeau Qld 4208
sales@brtfireandrescue.com.au

www.brtfireandrescue.com.au